4MP, TRUE DAY/NIGHT, WDR, IR, TURRET





4MP Fixed Lens Turret

IPT4B28X

- > Fully Adheres to National Defense Authorization Act (NDAA) Guidelines
- > Exceptional Video Quality with 4MP, 2560 x 1440 Resolution
- > Super-Efficient H.265 Video Compression for Drastically Reduced Bandwidth and Storage Requirements
- > Powerful, Smart IR LED Lights for 0 Lux Night Time Operation up to 98 Feet
- > 2.8mm fixed, wide-angle lens
- > TRUE Day/Night and WDR functionality for all Lighting Conditions
- > Backlight Compensation, Defog and 3D DNR (Digital Noise Reduction)
- > Dual Video Streams; ONVIF Profile S Compliant and built-in Microphone
- > Built-in Micro-SD Card Slot enables local storage up to 128GB
- > Intrusion Detection Analytics
- > 3-Way Axis, IP67 Weather Resistant Housing
- > PoE & 12VDC Power Options
- > Supported by uniview tec Guard Station Software and Guard Viewer Mobile App's for iPhone and Android Device

www.univiewtechnology.com



IPT4B28X TURRET



Specifications

Camera					
Sensor	1/2.9" 4MP, progressive scan CMOS				
Minimum illumination	Color: 0.01 lux (F2.0, AGC ON); 0 lux with IR on				
True Day / Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto / Manual, 1 ~ 1/100000s				
Adjustment angle (3-way Axis)	Pan: 0° ~ 360°; Tilt: 0° ~ 75°; Rotate: 0° ~ 360°				
WDR	120dB				
S/N	>52dB				
Lens	1				
Lens	2.8mm @ F2.0				
Iris	Fixed				
Field of View (H)	101.5°				
Field of View (V)	55.6°				
Field of View (O)	111.6°				
DORI					
DORI Distance	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	
	63	25.2	12.6	6.3	
Illuminator					
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main profile, High profile				
Frame Rate	Main Stream: 4MP (2560 x 1440), Max 30fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps; 720P (1280 x 720), Max 30fps Sub Stream: D1 (720 x 576), Max 30fps; 640 x 360, Max 30fps; 2CIF (704 x 288), Max 30fps; CIF (352 x 288), Max 30fps				
Video Bit Rate	128 Kbps~16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Video Stream	Dual				

Image		
White Balance	Auto / Outdoor / Fine Tune / Sodium Lamp / Locked / Auto2	
Digital Noise Reduction	2D / 3D DNR	

Uniview Technology / 850 Freeport Pkwy, Ste. 100, Coppell, TX 75019 Toll Free: 888-288-7644 / Main 972-459-8645 / Fax 972-459-8661 ©2024 uniview tec All rights reserved. Specifications and Design are subject to change without notice. UVT70270124-01



IPT4B28X TURRET




Smart IR	Supported		
Flip	Normal / Vertical / Horizontal / 180° / 90°Clockwise / 90°Anti-clockwise		
HLC	Supported		
BLC	Supported		
Defog	Digital Defog		
Intrusion Events			
Basic Detection	Motion detection, Ultra motion detection, tampering alarm, audio detection		
General Function	Watermark, IP address filtering, tampering alarm, alarm input, alarm output, access policy, ARP protection, RTSP authentication, user authentication		
Storage			
Edge Storage	Micro SD, up to 128GB		
Network Storage	ANR		
Network			
	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS,		
Protocols	SSL/TLS, SNMP		
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API		
User/Host	Up to 32 users. 2 user levels: administrator and common user		
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF		
Client	Guard Station, Guard Viewer		
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above; Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above		
Interface			
Built-in Mic	Support		
Network	1 * RJ45 10M/100M Base-TX Ethernet		
General			
Power	DC 12V±25%, PoE (IEEE 802.3af); Power consumption: Max 4W		
Power Interface	Ø 5.5mm coaxial power plug		
Dimensions (Ø × H)	Ø 118 x 96mm (Ø 4.6 x 3.8")		
Weight	0.30kg (0.66lb)		
Material	Metal + Plastic		
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)		
	4KV		
Surge Protection	4KV		



IPT4B28X TURRET

Dimensions



Accessories

See Camera Accessories Guide

