

HDMI Output Decoder Cards



4 & 7-ch Decoder Cards

FB-HD04-B-NB

FB-HD07-B-NB

- > Support 4 or 7 channels of additional HDMI outputs
- > For use in video walls
- > Supports NR6416X & NR12816X network recorders only
- > HDMI resolution up to 4K, 3840 x 2160
- > H.265 & H.264 standards support
- > Up to 16MP Resolution Recording

Specifications

Dimensions

Video Test Monitor	
HDMI Port	Supports 4 or 7 ch
HDMI Output 4-ch	<p>HDMI1 & HDMI2: 4K (3840x2160) 60Hz, 4K (3840x2160) 30Hz, 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p> <p>HDMI3 & HDMI4: 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p>
HDMI Output 7-ch	<p>HDMI1 & HDMI2 & HDMI3 & HDMI4: 4K (3840x2160) 60Hz, 4K (3840x2160) 30Hz, 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p> <p>HDMI5 & HDMI6 & HDMI7: 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p>
Camera Capability (fps): 4-ch	4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 64x 720P@30
Camera Capability (fps): 7-ch	<p>HDMI1 & HDMI3 & HDMI5 & HDMI7: 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 72x 720P@30, 112 x D1</p> <p>HDMI2 & HDMI4 & HDMI6: 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 72x 720P@30, 112 x D1</p>
Multi-window	1/4/5/6/7/8/9/16
Working Temperature	-10°C to +55°C (14°F to +131°F)
Working Humidity	10% ~ 90% (non-condensing)
Weight	1 Kg (2.2 lb)

